GERRITS TRUCKS & MACHINERY

WACKER NEUSON 38Z3 E07-01 Migraver 6718H 3 buckets

General characteristics

Brand	WACKER NEUSON
Subcategory	Mini digger crawler
Year of construction	2012
Hours displayed	6719
Condition	Used
General state	Very good
CE marking	Yes













Properties

Single weight	4.021kg

Technical specifications

Drive	tracking

Description

WACKER NEUSON 38Z3 MINI EXCAVATOR – 2012 – WITH TILT UNIT AND THREE BUCKETS Wacker Neuson 38Z3 mini excavator with enclosed cab, rubber tracks, hydraulic dozer blade and hydraulic tilt unit with quick coupler. Compact Zero Tail design, suitable for earthmoving, trenching and grading. Supplied with three buckets: 1.20 metres, 60 cm and 40 cm wide. Make: Wacker Neuson Model: 38Z3 Year of manufacture: 2012 Serial number: AG06887 Type / version: E07-01 Hour meter reading: approximately 6,718.3 hours Operating weight: 4,021 kg Transport weight: 3,849 kg Engine power: 21.4 kW / approximately 29 metric HP CE marking: present Engine: Yanmar 3TNV88 Fuel: diesel Number of cylinders: 3* Displacement: 1,642 cm^{3}* Cooling: water-cooled* Rated engine speed: 2,400 rpm* Electrical system: 12 V* Fuel tank capacity: 44 litres* Upper carriage design: Zero Tail, with no rear overhang* Upper carriage: 360° rotation Slewing speed: approximately 8.8 rpm* Boom: hydraulically offset Boom swing angle, left: 70°* Boom swing angle, right: 55°* Undercarriage: tracked Tracks: rubber Track width: 300 mm* Track rollers: 4 per side* Travel speeds: approximately 2.8 and 4.6 km/h* Ground clearance: approximately 280 mm* Dozer blade: hydraulically operated Blade width: approximately 1,740 mm* Blade height: approximately 345 mm* Hydraulic working pressure: 240 bar* Pump flow: 2 × 40 + 26.3 + 11.3 litres/minute* Hydraulic tank capacity: 38.5 litres* Hydraulic oil cooler: fitted* Auxiliary hydraulic connections on dipper arm: fitted Attachment system: hydraulic tilt unit with quick coupler Tilt unit manufacturer: Ullmann Type according to identification plate: HUM10-AH Attachment weight according to identification plate: 95 kg Pressure stated on attachment plate: 21 MPa / 210 bar Cab: enclosed Controls: twin joysticks and travel levers Operator's seat: adjustable, with armrests Seat belt: fitted Ventilation: fitted Radio: fitted Windscreen wiper: fitted Work lights: fitted Transport length: approximately 4.80 metres* Machine width: approximately 1.74 metres* Transport height: approximately 2.50 metres* Maximum digging depth: approximately 3.10–3.35 metres* Maximum reach: approximately 5.30–5.54 metres* Maximum digging height: approximately 4.53–4.66 metres* Maximum dumping height: approximately 3.22–3.35 metres* Bucket breakout force: approximately 28.6 kN* Dipper arm digging force: approximately 19.4–21.9 kN* Supplied with three buckets: 1 × bucket, 1.20 metres wide 1 × bucket, 60 cm wide 1 × bucket, 40 cm wide

Gerrits Trucks & Machinery Tinbergenstraat 2 7102
JL Winterswijk Nederland

+31 (0) 543 530199